

Injectable Microchips



TECHNICAL SPECIFICATIONS

Physical	Diameter: 1.4 mm \pm 0.16 mm / Length: 8.5 mm \pm 0.6 mm Diameter: 2.0 mm \pm 0.15 mm / Length: 12.0 mm \pm 0.4 mm Material: BIO GLASS 8625. Colour: Transparent
Electrical	Operating frequency: 134.2 KHz \pm 3 KHz
Chemical	Water immersion IP68 Aqueous solution of salts, Alcohol, Oil, HLC(10%), Ammoniac
Mechanical	Shock: IEC 68-2-29 Vibration : IEC 68-2-6
Thermal	Storage: -40°C a 90°C Peak temperature: +120°C . Operating: -25°C a 85°C
Others	Manufacturer's code ICAR 941 Coded according to ISO 11784 and 11785. FDX-B

CERTIFICATES

- Felixcan is compliant with the International Standard Organization Rules and Regulations in terms of the ISO9002 quality norm. As a result of this, Felixcan has been granted by AENOR in Spain and IQNET internationally with several quality certificates for the "Design, Production and Marketing of Electronic Animal Identification Systems".

CONTACT

- Polígono Industrial Romica, calle 1, Parcela 200, 02080 ALBACETE (España)
- Tlf.: +34 967 52 01 87 Fax: +34 967 52 20 61
- www.felixcan.com admin@felixcan.com